



Firma: PROSET VTT doo
Adresa: Miljkovačka 16
Telefon: 063/34-26-29
Fax: 063/34-26-29
PIB: 111703442
E-mail: prodaja@bktuning.rs

Kamera za rikverc MITSUBISHI Pajero / L200 (2001+)

Šifra: G6218

Kategorija proizvoda: MITSUBISHI

Proizvođač: OEM

Cena: **4.500,00** rsd.

Image Sensor	CMOS PC1030	CCD OV7959	CCD PC3030	CCD PC 7070	CCD PC1089K	CCD MT 9V136
TV System	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC
Effective Pixels	648*488Pixels	648*488	728(H)*488(V)	928(H)*500(V)	928(H)*500(V)	720*576/480Pixels
Horizontal resolution	420TVL	420(TV Line)	480TVL	500TVL	500TVL	480TVL
Sensing area	4.08mm*3.12mm	4008 um x 3024 um	3.584mm*2.688mm	3.584mm*2.688mm	3.584mm*2.688mm	3.584mm*2.688mm
Shutter speed	1/60-1/5000	1/60-1/5000	1/60-1/20000	1-1/10000	1-1/10000	1-1/10000
Minimum illumination	0.1LuxF=1.2(OLux with ON)	0.8Lux	0.1LuxF=1.2(OLux with ON)	0.01LuxF=1.2(OLux with OR ON)	0.01LuxF=1.2(OLux with OR ON)	0.01LuxF=1.2(OLux with OR)
Video output	1.0Vp-Pat 75 ohm	1.0vp-p.75 Omega	1.0Vp-Pat 75 ohm	1.0Vp-Pat 75 ohm	1.0Vp-Pat 75 ohm	1.0Vp-Pat 75 ohm
Power Supply	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V
Operating temperature	-20°C-75°C, RH 95%MAX	-20°C-75°C, RH 95%MAX	-20°C-75°C, RH 95% MAX	-20°C-75°C, RH 95% MAX	-20°C-75°C, RH 95% MAX	-20°C-75°C, RH 95% MAX
Storage temperature	-40°C-85°C, RH 95% MAX	-40°C-85°C, RH 95% MAX	-40°C-85°C, RH 95% MAX	-40°C-85°C, RH 95% MAX	-40°C-85°C, RH 95% MAX	-40°C-85°C, RH 95% MAX
Lens angle	170°	170°	170°	170°	170°	170°
Waterproof	IP69K	IP68	IP69K	IP69K	IP69K	IP69K
White Balance	auto	auto	auto	auto	auto	ato
AGC	Auto	Auto	Auto	Auto	Auto	Auto
BLC	Auto	Auto	Auto	Auto	Auto	Auto